

# ARGOSY

## STANDARD SPECIFICATIONS

### CHASSIS

- Chevrolet Motorhome chassis, 350 or 454 V8 engine (454 standard on 28' model).
- New front suspension providing passenger-car type handling with reinforced control arms, crossmember, stronger control arm shaft and auxiliary air springs.
- Front disc brakes and rear drum brakes with improved brake lining material.
- High ratio brake pedal for reduced pedal effort.
- Frame-mounted master cylinder.
- Hydro-Boost brake system using hydraulic pressure from power steering pump providing passenger-car type performance.
- In-line canister-type fuel filter.
- Front access fill, remote reservoir, for power steering pump.
- Gauge-type instrument cluster.
- Turbo Hydramatic 3-speed transmission.
- Power steering with tilt column.
- 72 amp hour battery.
- 61 amp Delcotron generator.
- Dual rear wheels, all models.
- Hydraulic jack and tire tools.
- Insulated wheel wells with sound-retardant covering.
- Tinted windshield.
- Recirculating air heater, separate blower, separate passenger control.
- Outside access to engine water fill, oil fill, windshield washer fluid and batteries.
- Electric windshield wipers and washers.
- Blade-mounted windshield washers.
- Fire Extinguisher.

### DRIVER'S COMPARTMENT

- Contoured, padded A.B.S. dash.
- Arm rests, both sides, both seats.
- Built-in headrests.
- Cigarette lighter.
- Ash tray.
- Inside rear-view mirror.
- Twin outside rear-view mirrors.
- Wrap-around windshield.
- Deluxe contoured swivel seats for driver and passenger; extra back and seat cushioning on driver's seat.
- Glove compartment and tilt-out beverage holder.
- Dash-mounted step, aisle, map, and trunk light controls.

### BASIC SHELL CONSTRUCTION

- Patented monocoque air flow aerodynamic shape.
- Extruded aluminum bumpers.
- Rectangular dual headlights.
- Hand-riveted monocoque shell of structural alloy aluminum.
- Exterior painting of Centauri Dupont enamel.
- Ribs of stretch-formed structural alloy aluminum.
- Cab frame of structural alloy aluminum with heavy-duty aluminum extruded roll bar.
- Interior walls of wear-resistant vinyl laminated to aluminum.
- Roomy wardrobes in all models.
- Spacious storage lockers.
- Color-coordinated interiors.
- Multiple roof fresh air vents.
- Easy roll-up tambour doors on all cabinets.
- Converta-Lux lounge (standard on 20' and 24' side-bath models).
- New Mark IV lounge (standard on 20' and 28' models).

- One-piece stretch-formed extruded aluminum window frames riveted to body.
- Exclusive contoured sliding and fixed windows of Herculite safety glass.
- Exclusive touch control aluminum fold-away entrance step.
- Awning rail.
- 2¼-inch aircraft-type fiberglass insulation.
- Adjustable no-draft aluminum roof vents.
- Outside storage areas.
- Super Panoramic laminated safety glass tinted windshield.
- Super Panoramic rear windows of Herculite safety glass (side-bath models).

### ELECTRIC EQUIPMENT

- A.N.S.I. ("R.V.I.A.") D.O.H. and C.S.A. code approved wiring system.
- Built-in 110V service line extends 20 feet.
- 72 amp hour battery for living area with automotive charging when driving or Univolt charging when plugged into 120V city power or when 120V optional power plant is in operation.
- Univolt ceiling lights.
- Ferro resonant Univolt to convert 110V city power to 12V direct current power.
- Overload safety fuse cartridges on Univolt wiring system.
- Circuit breakers on 110V wiring system.
- Sealed and vented battery compartment.

### PLUMBING

- A.N.S.I. ("R.V.I.A.") D.O.H. and C.S.A. code approved plumbing system.
- Lockable water fill.
- Univolt marine pump.

- Water tank capacity: 35 gallons for 20' models; 44 gallons for 24' and 28' models.
- City water inlet hook-up.
- Swing faucet and double galley sinks.
- Stainless steel galley sinks.
- Exclusive all thermo-formed bathroom with stall shower.
- Built-in medicine chest and mirror.
- Panoramic roof lockers.
- Water saver "telephone" shower head.
- Mechanically sealed flush toilet.
- Drainage drop-out cover cap with all-plastic drain valve for each tank.
- Built-in sewer hose carrier.

#### L.P. GAS EQUIPMENT

- A.N.S.I. ("R.V.I.A.") D.O.H. and C.S.A. code approved gas system.
- All gas equipment UA, AGA and/or C.S.A. approved.
- 50 lb. frame-mounted LPG gas bottle with Safety Overfill Valve.

- Sealed outside vent, with forced air, gas furnace with heat ducts. Input ratio: 25,000 BTU 20'; 30,000 BTU 24' and 28'.
- Automatic heater wall thermostat.
- Built-in igniter for space heater.
- Univolt blower and circulating ducts for space heater.
- Gas/electric combination refrigerator.
- Gas range with oven and broiler.
- Range vent exhaust hood.
- Fast-recovery six-gallon water heater.

#### FURNISHINGS

- Exclusive furniture construction of scratch-resistant vinyl and color-anodized aluminum extrusions.
- Lightweight, warp-free hollow core doors.
- PosiLock latches on all cabinet doors.
- Under-bed storage with drawers of lightweight high-impact styrene.
- Silverware drawer.

- Foam mattresses for all upholstery with zipped covers.
- All upholstery is nylon material with ScotchGard repeller to resist soiling. Shag nylon carpeting with pad in all areas.
- All draperies fade-resistant and pre-shrunk.
- All draperies lined.
- Decorator style washable vinyl window shades at galley and bathroom windows.
- All materials meet applicable flammability specifications.
- Twin bed bolster backs upholstered (2).

#### DIMENSIONS

- Outside height (with air conditioner): 20' and 24' models, 10'; 28' model, 10'2".
- Inside height, floor to ceiling: 6'7".
- Ground clearance: 20' and 24' models, 13" to underbelly, 7" to differential low point; 28' model, 14½" to underbelly, 9" to differential low point.

## OPTIONS

#### EXECUTIVE GROUP

- 50 gallon fuel tank (standard on 28' model). \*\*
- Rear end stabilizer.
- Hitch platform.
- Tinted windows.
- Screen door.
- Automotive air conditioner.

#### CONVENIENCE GROUP

- Univolt ceiling fan.
- Univolt stove exhaust fan.
- Entrance light.
- Central control system.
- Compartment lights.
- Combination sink covers and cutting boards.
- Toilet water saver spray.\*

#### SAFETY GROUP

- Outside floodlight.
- Headlight warning system.
- Emergency warning triangle.
- Auxillary main step extension.
- Four-wheel disc brakes.

#### DELUXE GROUP

- Solardome.\*
- Deluxe wheel covers.
- Cruise control.

#### ENTERTAINMENT GROUP

- Built-in stereo AM/FM radio, 4 speakers, w/8 track stereo tape deck, with or without CB radio.
- TV antenna, UHF, VHF, and color adapter, includes TV jack with 12V outlet.
- Telescoping radio antenna.

#### ROAD GROUP

- 10' Plasiflex sewer hose and clamps.
- 25' 5/8" water hose.
- Water "Y" for rally hook-up.

#### GENERAL OPTIONS

- Bolster bunk beds — 72".
- 10 cu. ft. gas/electric refrigerator.\* \*\*
- Pillow covers (2).
- Bedspreads (2).

- Wall comfort covers.
- New Mark IV lounge.\*\*
- Roof air conditioner.
- Fuel vapor emission controls (required on Calif. motorhomes).
- Spare wheel, tire, carrier, and cover.
- Nutone food center.\*\*
- Water purifier.
- Central vacuum cleaner.
- Adjustable towel rack.
- 120V generator, 4000W (Onan).
- 454 engine (standard on 28' model).\*\*
- Travel table.
- 65 lb. propane tank.\* \*\*
- Front and rear bumper guards.

\* Denotes exchange for standard equipment. All specifications and prices are based on the latest product information available at the time of publication. The right is reserved to make changes at any time in prices, colors, material, equipment, specifications, and models, and also to discontinue or add models.

\*\* Not available on some models.

# STANDARD SPECIFICATIONS

## CONSTRUCTION

Aerodynamic Air-Flow contoured shape.  
Gas electro-welded high-strength steel carriage.  
Torque rubber torsion bar axles.  
Shock absorbers on all wheels.  
Aluminum wheels on 22', 24', 26', and 28'.  
Electric brakes on all wheels — can be activated with foot brake pedal in car.  
Duck type extra strength wheels with 7:00 x 15 tubeless tires (D-rated on single axle models; E-rated on double axle models).  
Riveted monocoque shell.  
Corrosion protection: Automotive type alkyd enamel.  
Extruded stretch-formed structural alloy aluminum.  
Interior walls of wear-resistant vinyl laminated aluminum.  
Extruded stretch-formed extruded aluminum window frames riveted to body.  
Aerodynamic contoured Jet-Seal awning-type Herculite glass windows.  
Aerodynamic front windows using super strength lightweight safety glass.  
Weatherproof screens in all windows.  
Aerodynamic touch control fold away aluminum entrance step.  
Ramp rail.  
Double walled fiberglass insulated wheel wells.  
Aircraft type fiberglass insulation.  
Removable no draft aluminum roof vents.  
Aluminum steel wheels.

## OPTIONAL EQUIPMENT

Electric, D.O.H., C.S.A. and N.E.C. code approved lighting system.  
Plug weatherproof car trailer connector (includes 12 volt charge line).  
Light bulb, corrosion proof 180° visibility exterior clearance and running lights (installed in accordance with Federal Motor Vehicle Safety Standard 108).  
Automatic electric break-away switch.  
Map lights.

- Built in 110 volt service line (25 feet).
- Extra capacity 72 amperes hour 12 volt battery; built in sealed and vented battery compartment.
- Three position Univolt 4 bulb ceiling lights.
- One knob variable position ceiling vents.
- Exclusive ferro resonant Univolt to convert 110 volt city power to 12 volt direct current power and automatically charge battery.
- Overload safety fuse cartridges in Univolt wiring system.
- High intensity adjustable reading lights.
- Circuit breakers on 110 volt wiring system.
- Polarity warning light.

## PLUMBING

- A.N.S.I., D.O.H. and C.S.A. code approved plumbing system.
- High volume water pressure regulator in water inlet line.
- Univolt water pump.
- 30 gallon polyethylene water tank.
- Swing faucet at galley sinks.
- Stainless steel galley sinks.
- Exclusive all thermo formed bathroom with bathtub in rear bath 26', 28', shower room in 22', 24' and 28' center bath.
- Built in medicine chest and mirror.
- Telephone shower head.
- Mechanical seal toilet.
- Polyethylene holding tanks.
- Drainage drop out cover cap.
- Drainage drop out elbow for connecting sewer hose.
- Built in sewer hose carrier.
- Accessible dump valve.
- Lockable, flush water fill.

## GAS EQUIPMENT

- A.N.S.I., D.O.H. and C.S.A. code approved gas system.
- All gas equipment U.L. or A.G.A. and C.S.A. approved for use in travel trailers.
- Double five gallon gas bottles with rack.

- Sealed outside vented heater (input ratings: 22' = 16,000 BTU; 24', 26', 28' = 22,000 BTU).
- Automatic heater thermostat.
- Univolt sealed combustion system with forced air circulating ducts.
- Gas/electric combination refrigerator: 4.5 cubic foot in 22'. 6.0 cubic foot in 24', 26' and 28'.
- Gas range with oven and broiler.
- Range vent hood.
- 6 gallon gas water heater.

## FURNISHINGS

- Exclusive Perma-Tech furniture construction featuring heat treated anodized aluminum framework with textured vinyl panels.
- Lightweight warp free hollowcore doors.
- Tambour doors in all roof lockers.
- Tambour cabinet doors.
- Posi-Lok latches on all cabinet doors.
- Lightweight injection molded drawers.
- Credenza table in all models with front travel lounge.
- Bedroom wall comfort covers.
- Foam mattresses in bedroom with zippered covers.
- Nylon shag carpet in all areas.
- All upholstery treated with SCOTCHGARD repeller to resist soiling.
- All draperies fade resistant.
- Decorator styled washable vinyl window shades at galley and bathroom windows.
- Lined drapes.
- Slide away bathroom door.
- Bedroom vinyl folding door. (24', 26' and 28' only).
- Choice of three color schemes.
- Fire extinguisher.

## DIMENSIONS

- Outside floor width . . . 7'8".
- Outside height from ground . . . 8'10".
- Inside height (floor to ceiling) . . . 6'7".
- Ground clearance . . . 16" to underbelly. 12.24" to axle tube.
- Recommended hitch ball height . . . 19½".
- All specifications subject to change without notice.